



SPECIFICATION

SERIES No.	NOMINAL FREQUENCY MHz	POLE	PASSBAND		ATTENUATION BAND		RIPPLE MAX. dB	LOSS MAX. dB	ATTENUATION GUARANTEED		TERMINAL IMPEDANCE ohm // pF	OPERATING TEMPERATURE °C	CASE QTY.
			dB	kHz	dB	kHz			dB	FO ~ ±kHz			
21M7A	21.400	2	3	±3.75	20	±18.0	0.5	1.5	35 50	+350 ~ +1000 -200 ~ -1000	850 // 6.0	-20 ~ +70	1
21M7B	21.400	4	3	±3.75	40	±14.0	1.0	2.5	65 80	+350 ~ +1000 -200 ~ -1000	850 // 5.0	-20 ~ +70	2
21M12A	21.400	2	3	±6.0	20	±25.0	0.5	1.5	35 50	+350 ~ +1000 -200 ~ -1000	1200 // 3.0	-20 ~ +70	1
21M12B	21.400	4	3	±6.0	40	±20.0	1.0	2.5	65 80	+350 ~ +1000 -200 ~ -1000	1200 // 2.5	-20 ~ +70	2
21M15A	21.400	2	3	±7.5	18	±25.0	0.5	1.5	35 50	+350 ~ +1000 -200 ~ -1000	1500 // 2.0	-20 ~ +70	1
21M15B	21.400	4	3	±7.5	40	±25.0	1.0	2.5	65 80	+350 ~ +1000 -200 ~ -1000	1500 // 2.0	-20 ~ +70	2
21M20A	21.400	2	3	±10.0	18	±34.0	0.5	2.0	35 50	+500 ~ +1000 -200 ~ -1000	1800 // 1.5	-20 ~ +70	1
21M20B	21.400	4	3	±10.0	40	±34.0	1.0	2.5	65 80	+350 ~ +1000 -200 ~ -1000	1800 // 1.5	-20 ~ +70	2
21M30A	21.400	2	3	±15.0	15	±45.0	0.5	1.5	35 45	+350 ~ +1000 -300 ~ -1000	3000 // 0.5	-20 ~ +70	1
21M30B	21.400	4	3	±15.0	40	±50.0	1.0	2.5	65 80	+350 ~ +1000 -300 ~ -1000	3000 // 0.5	-20 ~ +70	2
21M30A2	21.400	2	3	±15.0	15	±45.0	0.5	1.5	35 45	+350 ~ +1000 -300 ~ -1000	1500 // 1.5	-20 ~ +70	1
21M30B2	21.400	4	3	±15.0	40	±50.0	1.0	2.5	65 80	+350 ~ +1000 -300 ~ -1000	2000 // 0.5	-20 ~ +70	2

PLEASE CONTACT OUR SALES DEPARTMENT FOR ADDITIONAL REQUIREMENTS.

