



SPECIFICATIONS

Series No.	Nominal Frequency (MHz)	Pole	Pass Band		Attenuation Band		Ripple (dB max.)	Loss (dB max.)	Attenuation Guaranteed		Terminal Impedance (ohm // pF)	Operating Temperature °C	Case Qty.
			(dB)	(kHz)	(dB)	(kHz)			(dB)	F0 ~ ±kHz			
21M7A	21.400	2	3	±3.75	20	±18.0	0.5	1.5	35 50	+350 ~ +1000 -200 ~ -1000	850 // 6.0	-20 ~ +70	1
21M7B	21.400	4	3	±3.75	40	±14.0	1.0	2.5	65 80	+350 ~ +1000 -200 ~ -1000	850 // 5.0	-20 ~ +70	2
21M12A	21.400	2	3	±6.0	20	±25.0	0.5	1.5	35 50	+350 ~ +1000 -200 ~ -1000	1200 // 3.0	-20 ~ +70	1
21M12B	21.400	4	3	±6.0	40	±20.0	1.0	2.5	65 80	+350 ~ +1000 -200 ~ -1000	1200 // 2.5	-20 ~ +70	2
21M15A	21.400	2	3	±7.5	18	±25.0	0.5	1.5	35 50	+350 ~ +1000 -200 ~ -1000	1500 // 2.0	-20 ~ +70	1
21M15B	21.400	4	3	±7.5	40	±25.0	1.0	2.5	65 80	+350 ~ +1000 -200 ~ -1000	1500 // 2.0	-20 ~ +70	2
21M20A	21.400	2	3	±10.0	18	±34.0	0.5	2.0	35 50	+350 ~ +1000 -200 ~ -1000	1800 // 1.5	-20 ~ +70	1
21M20B	21.400	4	3	±10.0	40	±34.0	1.0	2.5	65 80	+350 ~ +1000 -200 ~ -1000	1800 // 1.5	-20 ~ +70	2
21M30A	21.400	2	3	±15.0	15	±45.0	0.5	1.5	35 45	+350 ~ +1000 -300 ~ -1000	3000 // 0.5	-20 ~ +70	1
21M30B	21.400	4	3	±15.0	40	±50.0	1.0	2.5	65 80	+350 ~ +1000 -300 ~ -1000	3000 // 0.5	-20 ~ +70	2
21M30A2	21.400	2	3	±15.0	15	±45.0	0.5	1.5	35 45	+350 ~ +1000 -300 ~ -1000	1500 // 1.5	-20 ~ +70	1
21M30B2	21.400	4	3	±15.0	40	±50.0	1.0	2.5	65 80	+350 ~ +1000 -300 ~ -1000	2000 // 0.5	-20 ~ +70	2

Note: The above specifications are typical only. Please contact our Sales Department for specific requirements.

