



### SPECIFICATIONS

Series No.	Nominal Frequency (MHz)	Pole	Pass Band		Attenuation Band		Ripple (dB max.)	Loss (dB max.)	Attenuation Guaranteed		Terminal Impedance (ohm//pF)	Operating Temperature °C
			(dB)	(kHz)	(dB)	(kHz)			(dB)	F0 ~ kHz		
21SR7B	21.400	4	3	±3.75	10	±25.0	1	2	70	-910 ±10	Please contact us to discuss impedance with our Sales Department	-20 ~ +70
21SR15B	21.400	4	3	±7.50	10	±25.0	1	2	70	-910 ±10		-20 ~ +70
21SR30B	21.400	4	3	±15.0	10	±25.0	1	2	70	-910 ±10		-20 ~ +70
45SR7B	45.000	4	3	±3.75	10	±25.0	1	2	70	-910 ±10		-20 ~ +70
45SR15B	45.000	4	3	±7.50	10	±25.0	1	2	70	-910 ±10		-20 ~ +70
45SR30B	45.000	4	3	±15.0	10	±25.0	1	2	70	-910 ±10		-20 ~ +70
70SR7B	70.000	4	3	±3.75	10	±25.0	1	2	70	-910 ±10		-20 ~ +70
70SR15B	70.000	4	3	±7.50	10	±25.0	1	2	70	-910 ±10		-20 ~ +70
70SR30B	70.000	4	3	±15.0	10	±25.0	1	2	70	-910 ±10		-20 ~ +70
73SR7B	73.350	4	3	±3.75	10	±25.0	1	2	70	-910 ±10		-20 ~ +70
73SR15B	73.350	4	3	±7.50	10	±25.0	1	2	70	-910 ±10		-20 ~ +70
73SR30B	73.350	4	3	±15.0	10	±25.0	1	2	70	-910 ±10		-20 ~ +70

**Note:** The above specifications are typical only. Please contact our Sales Department for specific requirements.

