



Part Number	Centre Frequency (kHz)	Insertion Loss (dB) Max.	Pass Band Ripple (dB) Max.	6dB Bandwidth (kHz) Max.	50dB Bandwidth (kHz) Max.	Stop Bandwidth Attenuation $\pm 100$ kHz (dB) Min.	Input/Output Impedance ( $\Omega$ )
LTW33-450B	450 $\pm 2.0$	4	2	$\pm 15$	$\pm 30$	45	1500
LTW33-450C	450 $\pm 2.0$	4	2	$\pm 12.5$	$\pm 24$	45	1500
LTW33-450D	450 $\pm 1.5$	4	2	$\pm 10$	$\pm 20$	45	1500
LTW33-450E	450 $\pm 1.5$	6	2	$\pm 7.5$	$\pm 15$	45	1500
LTW33-450F	450 $\pm 1.5$	6	2	$\pm 6$	$\pm 12.5$	45	2000
LTW33-450G	450 $\pm 1.5$	6	2	$\pm 4.5$	$\pm 10$	45	2000
LTW33-450H	450 $\pm 1.0$	6	2	$\pm 3$	$\pm 9$	45	2000
LTW33-450I	450 $\pm 1.0$	6	2	$\pm 2$	$\pm 7.5$	45	2000
LTW33-450HT	450 $\pm 1.0$	6	2	$\pm 3$	$\pm 9$	60	2000
LTW33-450IT	450 $\pm 1.0$	6	2	$\pm 2$	$\pm 7.5$	60	2000

**Note:** The above specifications are typical only. Please contact our Sales Department for specific requirements.

