



| Part Number | Center Frequency (kHz) | Insertion Loss (dB) Max. | Pass Band Ripple (dB) Max. | 6dB Bandwidth (kHz) Max. | 50dB Bandwidth (kHz) Max. | Stop Bandwidth Attenuation ± 100 kHz (dB) Min. | Input/Output Impedance (Ω) |
|-------------|------------------------|--------------------------|----------------------------|--------------------------|---------------------------|--|-------------------------------------|
| LTM 450BU | 450 ± 2.0 | 4 | 2 | ± 15 | ± 30 | 27 | 1500 |
| LTM 450CU | 450 ± 2.0 | 4 | 2 | ± 12.5 | ± 24 | 27 | 1500 |
| LTM 450DU | 450 ± 1.5 | 4 | 2 | ± 10 | ± 20 | 27 | 1500 |
| LTM 450EU | 450 ± 1.5 | 6 | 2 | ± 7.5 | ± 15 | 27 | 1500 |
| LTM 450FU | 450 ± 1.5 | 6 | 2 | ± 6 | ± 12.5 | 27 | 2000 |
| LTM 450GU | 450 ± 1.0 | 6 | 2 | ± 4.5 | ± 10 | 25 | 2000 |
| LTM 450HU | 450 ± 1.0 | 6 | 2 | ± 3 | ± 9 | 25 | 2000 |
| LTM 450IU | 450 ± 1.0 | 6 | 2 | ± 2 | ± 7.5 | 25 | 2000 |
| LTM 450HTU | 450 ± 1.0 | 6 | 2 | ± 3 | ± 9 | 35 | 2000 |
| LTM 450ITU | 450 ± 1.0 | 6 | 2 | ± 2 | ± 7.5 | 35 | 2000 |

Note: The above specifications are typical only. Please contact our Sales Department for specific requirements.

