



Part Number	Center Frequency (kHz)	Insertion Loss (dB) Max.	Pass Band Ripple (dB) Max.	6dB Bandwidth (kHz) Max.	50dB Bandwidth (kHz) Max.	Stop Bandwidth Attenuation ± 100 kHz (dB) Min.	Input/Output Impedance (Ω)
LTM 455BU	455 ± 2.0	4	2	± 15	± 30	27	1500
LTM 455CU	455 ± 2.0	4	2	± 12.5	± 24	27	1500
LTM 455DU	455 ± 1.5	4	2	± 10	± 20	27	1500
LTM 455EU	455 ± 1.5	6	2	± 7.5	± 15	27	1500
LTM 455FU	455 ± 1.5	6	2	± 6	± 12.5	27	2000
LTM 455GU	455 ± 1.0	6	2	± 4.5	± 10	25	2000
LTM 455HU	455 ± 1.0	6	2	± 3	± 9	25	2000
LTM 455IU	455 ± 1.0	6	2	± 2	± 7.5	25	2000
LTM 455HTU	455 ± 1.0	6	2	± 3	± 9	35	2000
LTM 455ITU	455 ± 1.0	6	2	± 2	± 7.5	35	2000

Note: The above specifications are typical only. Please contact our Sales Department for specific requirements.

