



Part Number	Center Frequency (kHz)	Insertion Loss (dB) Max.	Pass Band Ripple (dB) Max.	6dB Bandwidth (kHz) Max.	50dB Bandwidth (kHz) Max.	Stop Band Att $\pm 100$ kHz (dB) Min.	Input/Output Impedance ( $\Omega$ )
LTM 450BW	450 $\pm 2.0$	4	2	$\pm 15$	$\pm 30$	45	1500
LTM 450CW	450 $\pm 2.0$	4	2	$\pm 12.5$	$\pm 24$	45	1500
LTM 450DW	450 $\pm 1.5$	4	2	$\pm 10$	$\pm 20$	45	1500
LTM 450EW	450 $\pm 1.5$	6	2	$\pm 7.5$	$\pm 15$	45	1500
LTM 450FW	450 $\pm 1.5$	6	2	$\pm 6$	$\pm 12.5$	45	2000
LTM 450GW	450 $\pm 1.5$	6	2	$\pm 4.5$	$\pm 10$	45	2000
LTM 450HW	450 $\pm 1.0$	6	2	$\pm 3$	$\pm 9$	55	2000
LTM 450IW	450 $\pm 1.0$	6	2	$\pm 2$	$\pm 7.5$	55	2000
LTM 450HTW	450 $\pm 1.0$	6	2	$\pm 3$	$\pm 9$	60	2000
LTM 450ITW	450 $\pm 1.0$	6	2	$\pm 3$	$\pm 7.5$	60	2000

**Note:** The above specifications are typical only. Please contact our Sales Department for specific requirements.

