



Part Number	Center Frequency (kHz)	Insertion Loss (dB) Max.	Pass Band Ripple (dB) Max.	6dB Bandwidth (kHz) Max.	50dB Bandwidth (kHz) Max.	Stop Bandwidth Attenuation ± 100 kHz (dB) Min.	Input/Output Impedance (Ω)
LTM 455BW	455 ± 2.0	4	2	± 15	± 30	45	1500
LTM 455CW	455 ± 2.0	4	2	± 12.5	± 24	45	1500
LTM 455DW	455 ± 1.5	4	2	± 10	± 20	45	1500
LTM 455EW	455 ± 1.5	6	2	± 7.5	± 15	45	1500
LTM 455FW	455 ± 1.5	6	2	± 6	± 12.5	45	2000
LTM 455GW	455 ± 1.5	6	2	± 4.5	± 10	45	2000
LTM 455HW	455 ± 1.0	6	2	± 3	± 9	55	2000
LTM 455IW	455 ± 1.0	6	2	± 2	± 7.5	55	2000
LTM 455HTW	455 ± 1.0	6	2	± 3	± 9	60	2000
LTM 455ITW	455 ± 1.0	6	2	± 3	± 7.5	60	2000

Note: The above specifications are typical only. Please contact our Sales Department for specific requirements.

