



Series Number	QSMO-2610 _{__} ⁽¹⁾	QSMO-2630 _{__} ⁽¹⁾	QSMO-2650 _{__} ⁽¹⁾	QSMO-2660 _{__} ⁽¹⁾
Frequency Range	32.768 kHz			
Overall Frequency Stability (Max) ⁽¹⁾	F = ±50ppm -40° to 85° P = ±100ppm -40° to 125°			
Storage Temperature Range	-40°C to +125°C			
Supply Voltage	3.3V	5.0V	1.8V	2.5V
Supply Current (Max)	260µA 2.8 ≤ V _{DD} ≤ 3.63V	280µA 3.63 ≤ V _{DD} ≤ 5.5V	240µA 1.6 ≤ V _{DD} ≤ 2.0V	252µA 2.0 ≤ V _{DD} ≤ 2.8V
Standby Current	At '0' Level at #1		20µA	
Output Voltage	"0" Level (Max) "1" Level (Min)		0.1V _{DD} 0.9V _{DD}	
Output Load (Max)	CMOS / TTL Load		15pF	
Rise/Fall Times (Max)	At 0.1V _{DD} ~ 0.9V _{DD}		50ns	
Symmetry (Max)	At 0.5V _{DD}		45% / 55%	
Start-Up Time (Max)	5ms			
Tri-State Control	#1 Open #1 ≥ 0.7V _{DD} #1 ≤ 0.3V _{DD}	#3 Active #3 Active #3 High Z		

Note (1): Customer to add 'F' or 'P' for Overall Frequency Stability.

Note: The above specifications are typical only. Please contact our Sales Department for specific requirements.

