



Series Number		QXO-9610	QXO-9630
Frequency Range		10 ~ 40 MHz	
Supply Voltage		+3.3V ±5%	+5.0V ±5%
Initial Calibration Tolerance		±500 ppb (max)	±500 ppb (max)
		V _{con} = +1.65V	V _{con} = +2.5V
Frequency Stability	vs. Temperature (refer to 25°C)	±10ppb (max) over -30°C to +70°C	
		±20ppb (max) over -40°C to +85°C	
	vs. Voltage Change	±10ppb (max) for a ±5% input voltage change	
	vs. Warm-up time (to 25°C)	5 minute maximum within ±0.1ppm of its reference frequency	
	vs. Aging	±3ppb max after 30 days ±600ppb max over one year ±3ppm max over 10 years	
Voltage Control On pin 1 (EFC) (Electronic frequency tuning)	vs. Reflow	±1.0ppm max. 1 reflow measured 24 hours afterwards	
	Frequency Deviation Range	> ±5ppm. Referenced to FO at ±25°C and over operating temperature range	
	Control Voltage Range	+1.65V ±1.65V	+2.5V ±2.5V
	Transfer Function	Positive: Increasing control voltage increases output frequency	
	Input Impedance	100 kΩ (min)	
EFC Linearity	±10% (max)		
Power Dissipation (at +25°C)		0.4 watts (max) at steady state; 350mA (max) at turn-on	
Output	Output Voltage Level (p-p)	+0.8V p-p (min)	
	Load	10kΩ // 10pF ±10%	
	Rise and Fall Time	7 ns (max) (from 20% to 80% of waveform)	
	Phase Noise Offset (10 MHz) (Typical)	10 Hz : -98 dBc 100 Hz : -126 dBc	1 kHz : -145 dBc 10 kHz : -152 dBc

Note: The above specifications are typical only. Please contact our Sales Department for specific requirements.

