



SPECIFICATIONS

Series No.	Nominal Frequency (MHz)	Pole	Pass Band		Attenuation Band		Ripple (dB max.)	Loss (dB max.)	Attenuation Guaranteed		Terminal Impedance (ohm//pF)	Operating Temperature °C	Case Qty.
			(dB)	(kHz)	(dB)	(kHz)			(dB)	F0 ~ kHz			
21SU7A	21.400	2	3	±3.75	18	±18.0	1.0	1.5	50	-910 ±10	850 // 6.0	-20 ~ +70	1
21SU7B	21.400	4	3	±3.75	35	±14.0	1.0	2.5	80	-910 ±10	850 // 3.5	-20 ~ +70	2
21SU15A	21.400	2	3	±7.50	15	±25.0	1.0	1.5	50	-910 ±10	1500 // 2.0	-20 ~ +70	1
21SU15B	21.400	4	3	±7.50	35	±25.0	1.0	2.5	80	-910 ±10	1500 // 0.5	-20 ~ +70	2
21SU20A	21.400	2	3	±10.0	15	±34.0	1.0	2.0	45	-910 ±10	1800 // 0.5	-20 ~ +70	1
21SU20B	21.400	4	3	±10.0	35	±34.0	1.0	2.5	80	-910 ±10	1800 // -1.0	-20 ~ +70	2
21SU30A	21.400	2	3	±15.0	15	±45.0	1.0	1.5	45	-910 ±10	3000 // 0	-20 ~ +70	1
21SU30B	21.400	4	3	±15.0	35	±50.0	1.0	2.5	80	-910 ±10	3000 // -1.5	-20 ~ +70	2
45SU7A	45.000	2	3	±3.75	10	±12.5	1.0	2.5	65	-910 ±10	300 // 10	-20 ~ +70	1
45SU15A	45.000	2	3	±7.50	15	±25.0	1.0	2.0	40	-910 ±10	650 // 4.5	-20 ~ +70	1
45SU20A	45.000	2	3	±10.0	15	±34.0	1.0	2.0	40	-910 ±10	700 // 3.0	-20 ~ +70	1
45SU30A	45.000	2	3	±15.0	15	±50.0	1.0	2.0	35	-910 ±10	800 // 1.5	-20 ~ +70	1

Note: The above specifications are typical only. Please contact our Sales Department for specific requirements.

