



SPECIFICATIONS

Series Number	QSMO-2110 ⁽¹⁾	QSMO-2150 ⁽¹⁾	QSMO-2160 ⁽¹⁾
Frequency Range	1.8 to 170 MHz	1.8 to 133 MHz	1.8 to 170 MHz
Overall Frequency Stability (Max) ⁽¹⁾	A = ±25ppm B = ±50ppm C = ±100ppm D = ±10ppm	0° to 70°	E = ±25ppm F = ±50ppm G = ±100ppm H = ±20ppm
Storage Temperature Range	-50°C to +125°C		
Supply Voltage	+3.3V ±5%	+1.8V ±5%	+2.5V ±5%
Supply Current (Max)	40mA	28mA	38mA
Standby Current	At '0' Level at #1 10µA		
Output Voltage	"0" Level (Max) 0.1V "1" Level (Min) 0.9V		
Output Load (Max) TTL Load, CMOS Load	15pF		
Rise/Fall Times (Max)	At 0.1V _{DD} ~ 0.9V _{DD} or 0.2V _{DD} ~ 0.8V _{DD} 6ns (0.1V _{DD} ~ 0.9V _{DD})		
Symmetry (Max)	At 0.5V _{DD} or 1.4V 45% / 55%		
Start-Up Time (Max)	5ms		
Tri-State Control	#1 Open #1 ≥2.2V or 0.7V _{DD} #1 ≤0.8V or 0.3V _{DD}	#3 Active #3 Active #3 High Z	

Note (1): Customer to add 'A' to 'D' or 'E' to 'H' for Overall Frequency Stability.

Note: The above specifications are typical only. Please contact our Sales Department for specific requirements.

